

CAUTION! - DO NOT APPLY TO THE FOLLOWING: WINDSHIELDS, DRIVER DOOR WINDOW GLASS OR PASSENGER SIDE DOOR WINDOW GLASS!!

EFFECTS OF CONDENSATION ON VISION QUALITY OF PERFORATED WINDOW FILMS: RAINFALL, SNOWFALL AND CAR WASHES CAN FILL THE SMALL PERFORATIONS AND CAUSE REDUCED VISION UNTIL DRYING OCCURS.

CONSULT YOUR LOCAL LAWS REGARDING THE APPLICATION OF WINDOW TINT TO VEHICLE GLASS.

DIRECTIONS FOR APPLYING YOUR NEW



WINDOW GRAPHIC TO EXTERIOR GLASS SURFACES.

Step 1: Prepare the Vehicle

If you cannot bring the vehicle into a heated building, make sure that the outside air temperature is above +40° F (+5°C). Pre-warming the car interior during cold weather application will help insure proper adhesion.

Step 2: Prepare the Glass

Clean the outside glass surface which you will be applying the image to thoroughly with soap and water. Make sure that the glass surface is dry and residue free before applying your GLASSCAPES™ window image. **Remember:** The pressure sensitive adhesive works best if mounted on VERY CLEAN GLASS.

Step 3: Position and Apply (WARNING - DO NOT USE A HEAT GUN OR WATER TO APPLY !!)

If applying a full size window image, use masking tape strips to pre-position the image on the vehicle prior to removing the backing material. Carefully peel off adhesive backing from behind the image and apply from one edge and work to the opposite side, smoothing the image to prevent wrinkles. To remove any wrinkles, gently lift up the image to where the wrinkle is, smooth out the wrinkle with your hand, and continue applying. GLASSCAPES are a dry mount product !

Step 4: Bond and Trim

To help adhesion, lay the disposable backing over the image and rub firmly from the center to the sides of the image. If mounting a full window GLASSCAPES image you will have extra material to trim outside of the edge of your rear window glass. Trim the excess material with an Exacto knife or similar tool to complete the installation. The pressure sensitive adhesive bonds to the glass very well when first applied but sets more firmly after a twenty-four (24) hour period. Avoid power car washes for the first week after application. For longer life avoid using snow scrapers on this image. Treat this image as you would the painted surface of your car. Do not use abrasive cleaners on the image. Rear window mounted wiper blades will cause premature wear of the image.

Removal Techniques - The perforated film can be removed by using a thin scraper device. It is best to start in one corner and lift up a small section. After this is done, you can normally use hand force to pull the image from the glass. As with any decal or sticker, the warmer the outside temperature, the easier the removal will be. If any adhesive residue remains on the glass surface it can be cleaned with any quality commercial glass cleaning liquid or citrus-based adhesive remover / cleaner.

GLASSCAPES™ © 2000, Woodward 1 Group, Farmington, MI 48332-0370, USA
GLASSCAPES window graphics are Made in America from One-Way Vision™ film
One-Way Vision™ is a trademark of Clear Focus Imaging, Inc.